

by Ryan J. Dexter, P.E.

BCSI recommendations for handling and installing large assemblies

Following the issue's theme of material handling, we recently received the following question from a component manufacturer.

### Question

A local contractor contacted me looking for information on lifting truss assemblies in place. He is working on a job where he would like to build a roof truss assembly on the ground and lift into place as a single unit. Is there general information available that we could provide to the contractor?

### Answer

BCSI provides guidelines for handling and installing a set of trusses by constructing an assembly on the ground and lifting it into place using the Alternate Installation Method. BCSI states that the contractor should be sure to install all top chord, web member, and bottom chord lateral restraint and bracing prior to lifting the assembly. (See photo at left.)

Truss assemblies are typically "picked" or lifted from approximately the one-third points of the truss span, but additional locations may be required for long-span trusses and odd truss or roof configurations. Because there are many variables involved in this process, BCSI states that the contractor should "be sure to get the proper Professional Engineering guidance to lift the entire system into place safely and efficiently." This is an important step as there may be additional restraint and bracing required to safely lift the truss units into place. (See photos at right.)

**The number of trusses that can be assembled and lifted at one time depends on several factors including the capacity of the crane, the availability and type of hoisting equipment and jobsite space and conditions, to name a few.**

Tips for building a set of long-span trusses into a stable base unit on the ground and then lifting into place is also provided. A few years back, *SBC Magazine* printed "Developing a Strategy for Long Span Truss Installation" in which the trusses were installed this way: [www.sbcmag.info/2004\\_longspan.pdf](http://www.sbcmag.info/2004_longspan.pdf).

The number of trusses that can be assembled and lifted at one time depends on several factors including the capacity of the crane, the availability and type of hoisting equipment and jobsite space and conditions, to name a few. If the structural sheathing for this roof assembly is 4'x8' sheets of OSB or plywood and the trusses are to be spaced at 2' on center, then the number of trusses in each module will be a multiple of 4 or 5 depending on the layout pattern for the sheathing. However, as you will see from the bottom photo on the facing page, much larger modules can be installed. **SBC**

To pose a question for this column, call the SBCA technical department at 608/274-4849 or email [technicalqa@sbcmag.info](mailto:technicalqa@sbcmag.info).



Ground Bracing for truss assembly being built on the ground.



Install Web Member Permanent Lateral Restraint and Diagonal Bracing (or web reinforcement) and Bottom Chord Permanent Lateral Restraint and Diagonal Bracing as required.



Sheathing and bracing was applied before hoisting this assembly of more than 20 trusses.

## The VIKING Combo-16

Framing & Sheathing on ONE Platform

Modular: 16' long or 60' long: we can build the length you need!



- Manual Stops
- Stud Locators 16" and 24" o/c
- Manual Frame Nailing
- Quick Disconnect Air Fittings for Hand Tools
- Automated Sheathing Nailing
  - Simple to Use Controls
  - Tilt Nailing
  - High Load Coil Capacity
  - Infinite o/c spacing
- Quick Change Tool Mounts
- 2x4, 2x6, and 2x8 capable
- Programmable for Under and Overhung Sheathing

Wall Panel Solutions That Fit Your Business Needs



Viking Wall Panel Systems  
800.328.3402  
[www.vikingeng.com](http://www.vikingeng.com)  
[info@vikingeng.com](mailto:info@vikingeng.com)

For reader service, go to [www.sbcmag.info/viking.htm](http://www.sbcmag.info/viking.htm)

## MASENGILL MACHINERY CO.

Production Machinery Specialists Since 1963

New • Used • Refurbished • Reconditioned

Over 50,000 sq. ft. warehouse filled with equipment to meet your needs:

- |   |   |   |
|---|---|---|
| 1 - ADT "FASTRAC" Bridge Nailer             | Gantry w/Auto-Stackers                                | with Koskovich Jet-Set Automation Hardware              |
| 2 - ADT Wall Panel Lines                    | 5 - Klaisler Powered Outfeed Roller Systems           | 1 - Pacific Automation Floor Gantry w/Auto-Stacker      |
| 1 - Alpine 14'6" Finish Roller              | 2 - Koskovich Auto-OMNI, 5 Heads with Ink Jet Printer | 1 - Paslode Model CN70 Sub Component Nailer             |
| 4 - Alpine Model 725D Finish Rollers(15'6") | 1 - Mango Tech "Wall Extruder" 2006                   | 1 - Robbins Valley Set Shaper                           |
| 1 - Alpine Speed Roll TW Floortruss Machine | 30 - Material Handling Carts (Steel)                  | 1 - Robbins 7 Station Lumber Carousel                   |
| 1 - ASI FWA-500 Floor Web Saw               | 2 - Monet B500 Component Saws                         | 1 - Speedcut MetraCut w/Mango Automation                |
| 5 - ASI Stretch Roller Bed Trailers         | 2 - Pacific Automation Auto 8's                       | 1 - Speedcut EWC Web Saw                                |
| 1 - ASI Roller Bed Trailer                  | 2 - Pacific Automation 5 Strand Live Decks            | 1 - Spida Model CXTM R/A Saw with Hain Measuring System |
| 2 - Clary 329 Short Cutters II              | 4 - Pacific Automation Auto-Roll 14TR Gantry Rollers  | 1 - TCT Model 1150 w/ Mathews Ink Jet System (2005)     |
| 1 - EMSI Model #305 20' Lumber Conveyor     | 1 - Pacific Automation Auto-Roll 14' capacity         | 1 - Weima Model 1300 "TIGER" Wood Grinder               |
| 60 - Factory Wagons                         | 1 - Klaisler RolSplice Machine                        |   |
| 1 - Jager TTS Auto Stackers                 | 2 - Pacific Automation 125' J-Slot Gantry Lines       |   |
| 2 - Klaisler G2450 Floor                    |   |   |



1002 Buffalo Trail • Morristown, TN 37814  
Office: (888)USE-WOOD (873-9663)  
Fax: (423)586-0483  
[info@masengills.com](mailto:info@masengills.com)

[www.masengills.com](http://www.masengills.com)

For reader service, go to [www.sbcmag.info/masengill.htm](http://www.sbcmag.info/masengill.htm)

# STRUCTURAL BUILDING **COMPONENTS**<sup>TM</sup>

THE FUTURE OF FRAMING

[www.sbcmag.info](http://www.sbcmag.info)

Dear Reader:

Copyright © 2010 by Truss Publications, Inc. All rights reserved. For permission to reprint materials from **SBC Magazine**, call 608/310-6706 or email [editor@sbcmag.info](mailto:editor@sbcmag.info).

The mission of **Structural Building Components Magazine (SBC)** is to increase the knowledge of and to promote the common interests of those engaged in manufacturing and distributing of structural building components to ensure growth and continuity, and to be the information conduit by staying abreast of leading-edge issues. SBC will take a leadership role on behalf of the component industry in disseminating technical and marketplace information, and will maintain advisory committees consisting of the most knowledgeable professionals in the industry. The opinions expressed in SBC are those of the authors and those quoted solely, and are not necessarily the opinions of any affiliated association (SBCA).



6300 Enterprise Lane • Suite 200 • Madison, WI 53719  
608/310-6706 phone • 608/271-7006 fax  
[www.sbcmag.info](http://www.sbcmag.info) • [admgr@sbcmag.info](mailto:admgr@sbcmag.info)